

Package

Last Modified on 04/18/2019 6:00 pm EDT

Package Object

Package is a Child List of [Ship Doc](#). Packages are used to assign ship doc items to certain boxes or pallets. Package is comprised of Package and an array of Package Items.

- [End Point](#)
- [Properties - Package](#)
- [Properties - Package Item](#)
- [Json Sample](#)

End Point

/package

GET, POST, DELETE

GET returns an Array of packages associated with a specific Ship Doc. Its only parameter is docNo.

DELETE's parameter is the Id of the Package.

[Top](#)

Properties - Package

Property	Caption	Data Type	Required
DocNo	No.	Int32	True
PackageNo	Package No	Int32	False Read only, auto assigned.

PackageCode	Code	String (50)	False
TrackingNo	Tracking No.	String (50)	False
Length	Length	Int32	False
Width	Width	Int32	False
Height	Height	Int32	False
Width	Width	Int32	False
PackageTypeRef	Package TypeRe	EntityRef	False
Details	Items	Array of Packageltem	True
CustomFields	Custom Fields	Array of CustomFieldData	False

[Top](#)

Properties - Package Item

Property	Caption	Data Type	Required	Read Only
Id	Id	Int32	False	False
LineNo	Line No	Int16	False	True
ItemRef	Item	EntityRef	True	True
LotOrSerialNo	Description	String (50)	True	False
LineInstructions	Line Instructions	String (4000)	False	False
SalesTaxCodeRef	Tax Code	EntityRef	False	False
UomRef	UOM	EntityRef	False	False

UomConversionRate	UOM Conversion Rate	Decimal	False	False
Price	Price	Decimal	True	False
Quantity	Quantity	Decimal	True	False
StdCost	Std. Cost	Decimal	False	True
StdPrice	Std. Price	Decimal	False	True

[Top](#)

Json Sample

```
{
  "DocNo": 1000164,
  "PackageCode": "759023509",
  "TrackingNo": "32425352525",
  "Length": 1.5,
  "Details": [
    {
      "ItemRef": {
        "Id": 1020
      },
      "LineNo": 1,
      "LotOrSerialNo": "",
      "Quantity": 1
    },
    {
      "ItemRef": {
        "Id": 1021
      },
      "LineNo": 2,
      "LotOrSerialNo": "5092347096729-0",
      "Quantity": 1
    }
  ]
}
```

[Top](#)

